

HEAVY DUTY CYCLONES

IMPERIAL
SYSTEMS, INC.

Our Cyclone Dust Collectors provide superior dust containment for a variety of applications.

Advantages

- **Engineered by the Dust Collection Experts**
- **Robust 12 Gauge Carbon Steel Construction**
- **Stitch Welded Interiors**

Features

- Custom engineering to meet specific applications
- Coned tops for rain run-off
- Fabricated from carbon steel, aluminum, stainless steel and AR plate
- Fully welded construction from 12 gauge to 3/8" plate on some models
- Used in a variety of industries
- 12" inspection door above material discharge
- Standard colors are Imperial white or tan

Three Standard Models

- IS-C Standard Efficiency:
120 CFM to 8,000 CFM
- IS-HE High Efficiency:
7,000 CFM to 45,000 CFM
- IS-UHE Ultra High Efficiency:
2,000 CFM to 13,000 CFM

Options

- Structural Supports custom engineered to meet customer's requirements
- Inlet and outlet transitions for duct connections
- Outlet dampers
- Vortex breaker / Expansion chamber
- Insulation for high temp applications
- Rubber lined body and cones for high abrasion applications
- Inlet linings out of AR plate, stainless steel, rubber, etc.
- Multiple inlets and back draft dampers
- Ceramic linings for high temp and abrasive applications
- Efficiency guarantee if required
- Particle laboratory testing
- Multi-clone model available

Imperial Systems, Inc. is your dust collection & air pollution control expert; from designing and installing dust collection systems to manufacturing industry leading products, engineered for outstanding quality, safety and value.

All of our products can be fabricated to meet specific needs.

300 Imperial Drive Jackson Center, PA 16133

Tel 800.918.3013 | Fax 724.662.2803

info@isystemsweb.com

www.isystemsweb.com

Disclaimer: Imperial Systems, Inc. is not responsible for typographical errors that may appear.



HEAVY DUTY CYCLONES



IS-C STANDARD EFFICIENCY: 120 CFM TO 8,000 CFM

MODEL	CFM	WEIGHT (LBS)	A	B	C	F	G	J	K	L	M	N	P
ISC13	100-300	80	13	6	6	5	4	11	17	4 7/16	3	8	26 9/16
ISC17	200-500	145	17	7 13/16	6	5 3/8	5	13 5/16	26 5/8	5 13/16	3 3/8	8	26 9/16
ISC20	300-700	200	20	9 3/16	6	6 5/16	6	15 11/16	29 1/16	6 13/16	4	8	26 9/16
ISC30	500-1200	380	30	13 3/4	10	9 1/2	8	23 1/2	45 5/8	10 1/4	6	12	40 3/4
ISC36	800-2200	550	36	16 1/2	10	11 3/8	10	28 3/16	58 1/2	12 5/16	7 3/16	12	40 3/4
ISC42	1200-3000	710	42	19 1/4	10	13 5/16	11	32 7/8	71 7/16	14 3/8	8 3/8	12	40 3/4
ISC51	1700-4000	1050	51	22 15/16	10	15 13/16	14	39 3/16	91 11/16	17 1/16	10	12	40 3/4
ISC60	2500-6000	1420	60	27 1/2	10	19	16	47	110 3/16	20 7/8	12	12	40 3/4
ISC68	3200-8000	1790	68	31 3/16	10	21 9/16	18	53 1/4	127 7/16	23 1/4	13 5/8	12	40 3/4



IS-H HIGH EFFICIENCY: 7,000 CFM TO 45,000 CFM

MODEL	CFM	WEIGHT (LBS)	A	B	C	D	E	F	G	H	I	J
ISH51	6200-8800	1309	51	205 3/4	108 1/8	49 7/16	165 5/8	193 1/8	13	31	16	16
ISH54	7200-10200	1437	54	213 11/16	113 3/4	49 7/16	171 1/4	199 3/4	15	31	18	18
ISH60	8600-12200	1693	60	240 3/8	124 15/16	49 7/16	193 7/16	225 7/16	15	37	19	19
ISH68	11000-15600	2072	68	270 1/4	140 1/8	49 7/16	218 1/8	253 5/8	17	42	21	21
ISH74	13200-18800	2374	74	292	151 5/16	49 7/16	234 13/16	273 5/16	19	45	24	24
ISH85	17700-25100	3104	85	333 7/16	171 13/16	49 7/16	268 13/16	312 5/16	22	52	27	27
ISH96	22800-32400	5576	96	378	194 3/8	76 13/16	304 7/8	353 7/8	25	59	31	31
ISH108	2860-40600	6883	108	420 7/16	216 3/4	76 13/16	340 3/4	395 1/4	28	66	35	35
ISH120	35600-50400	8400	120	469	239 1/4	76 13/16	378 1/4	438 3/4	32	74	39	39
ISH132	42700-60500	9682	132	512 7/16	261 5/8	76 13/16	414 1/8	479 5/8	34	81	42	42
ISH144	50500-71600	11369	144	556 15/16	284 1/16	76 13/16	450 1/16	521 1/16	37	88	46	46



IS-UHE ULTRA HIGH EFFICIENCY: 2,000 CFM TO 13,000 CFM

MODEL	CFM	WEIGHT (LBS)	A	B	C	D	E	F	G	H	J	K	P	R
ISUHE21	2100-2500	366	21	94 11/16	50 3/16	15	6	9 1/2	13 7/8	29 3/4	19	25 3/4	39 3/4	22 1/2
ISUHE24	2800-3200	454	24	108 9/16	56 13/16	18	6 1/2	10 3/4	15 1/8	32 13/16	21 1/2	25 3/4	46 3/8	27
ISUHE27	3500-4000	582	27	120 1/2	63 1/2	20	7 1/4	12	16 3/8	35 15/16	24	37 5/8	51	30
ISUHE30	4200-4800	689	30	132 3/8	70 1/8	22	8	13 1/4	17 5/8	38 15/16	26 1/2	37 5/8	55 5/8	33
ISUHE33	5300-6100	828	33	144 11/16	76 11/16	24	9 1/4	15	19 3/8	42	30	37 5/8	60 1/2	36
ISUHE36	6600-7600	945	36	153 5/8	81 1/8	25 1/2	10 3/4	16 1/2	20 7/8	45 1/16	33	37 5/8	64 1/4	38 1/4
ISUHE39	7700-8800	1132	39	174 3/16	97 7/16	27	11 3/4	17 3/4	22 1/8	48 1/16	35 1/2	39 7/16	67 7/8	40 1/2
ISUHE43	9400-10,800	1328	43	188 3/4	104	30	13	19 3/4	24 1/8	52 1/8	39 1/2	39 7/16	74 7/8	45
ISUHE47	10,200-12,600	1532	47	202 15/16	110 11/16	33	13 3/4	21 1/4	25 5/8	56 3/16	42 1/2	39 7/16	81 5/8	49 1/2



Drawings are for representation only.
Refer to certified sales drawings for accurate representation.

Proud Product Representative



300 Imperial Drive Jackson Center, PA 16133
Tel 800.918.3013 | Fax 724.662.2803
info@isystemsweb.com

www.isystemsweb.com

Disclaimer: Imperial Systems, Inc. is not responsible for typographical errors that may appear.